

الكلية التطبيقية السنة الثالثة

مقرر ويب ٢ العملي

المحاضرة الأولى

المصفوفات

مثال ١

1. <?
2. `$a=array("a","a","b","h","a","d","t");`
3. `$count=array_count_values($a);`
4. `foreach($count as $key=>$value)`
5. `{`
6. `print("$key: $value
 \n");`
7. `}`
8. `?>`

التنفيذ

a: 3

b: 1

h: 1

d: 1

t: 1

المصفوفات

مثال ٢

1. <?
2. `$a=array("a","a","b","h","a","d","t");`
3. `print("<pre>");`
4. `print_r($a);`
5. `print("</pre>");`
6. ?>

التنفيذ

Array (

[0] => a

[1] => a

[2] => b

[3] => h

[4] => a

[5] =>

d [6] => t)

المصفوفات

مثال ٣

1. <?
2. `$a=array(1=>"a","ss"=>"h",4=>"arab");`
3. `foreach(array_keys($a) as $key)`
4. `{`
5. `print("$key
 \n");`
6. `}`
7. `?>`

التنفيذ

1

SS

4

المصفوفات

مثال ٤

1. <?
2. `$a=array("a","a","b","h","a","d","t");`
3. `$b=array("a1","a1","b1","h1","a1","d1","t1");`
4. `$c=array_merge($a,$b);`
5. `print("<pre>");`
6. `print_r($c);`
7. `print("</pre>");`
8. ?>

التنفيذ

Array (

[0] => a

[1] => a

[2] => b

[3] => h

[4] => a

[5] => d

[6] => t

[7] => a1

[8] => a1

[9] => b1

[10] => h1

[11] => a1

[12] => d1

[13] => t1

)

المصفوفات

مثال ٥

1. <?
2. `$a=array("a","a","b","h","a","d","t");`
3. `$b=array_pad($a,15,zzz);`
4. `print("<pre>");`
5. `print_r($b);`
6. `print("</pre>");`
7. ?>

التنفيذ

Array (

[0] => a

[1] => a

[2] => b

[3] => h

[4] => a

[5] => d

[6] => t

[7] => zzz

[8] => zzz

[9] => zzz

[10] => zzz

[11] => zzz

[12] => zzz

[13] => zzz

[14] => zzz)

المصفوفات

مثال ٦

1. <?
2. `$a=array("a","a","b","h","a","d","t");`
3. `$b=array_pop($a);`
4. `print("<pre>");`
5. `print_r($a);`
6. `print("</pre>");`
7. ?>

التنفيذ

Array (

[0] => a

[1] => a

[2] => b

[3] => h

[4] => a

[5] => d)

المصفوفات

مثال ٧

1. <?
2. `$a=array("a","a","b","h","a","d","t");`
3. `$b=array_push($a,"f","z");`
4. `print("<pre>");`
5. `print_r($a);`
6. `print("</pre>");`
7. ?>

التنفيذ

Array (

[0] => a

[1] => a

[2] => b

[3] => h

[4] => a

[5] => d

[6] => t

[7] => f

[8] => z

)

المصفوفات

مثال ٨

1. <?
2. `$a=array("a","a","b","h","a","d","t");`
3. `$b=array_reverse($a);`
4. `print("<pre>");`
5. `print_r($b);`
6. `print("</pre>");`
7. ?>

التنفيذ

Array (

[0] => t

[1] => d

[2] => a

[3] => h

[4] => b

[5] => a

[6] => a)

المصفوفات

مثال ٩

1. <?
2. `$a=array("a","a","b","h","a","d","t");`
3. `$b=array_shift($a);`
4. `print("<pre>");`
5. `print_r($a);`
6. `print("</pre>");`
7. ?>

التنفيذ

Array (

[0] => a

[1] => b

[2] => h

[3] => a

[4] => d

[5] => t)

المصفوفات

مثال ١٠

1. <?
2. `$a=array("a","a","b","h","a","d","t");`
3. `$b=array_slice($a,2,3);`
4. `print("<pre>");`
5. `print_r($b);`
6. `print("</pre>");`
7. ?>

التنفيذ

Array

(

[0] => b

[1] => h

[2] => a

)

المصفوفات

مثال ١١

1. <?
2. `$a=array("a","a","b","h","a","d","t");`
3. `$b=array_unique($a);`
4. `print("<pre>");`
5. `print_r($b);`
6. `print("</pre>");`
7. ?>

التنفيذ

Array

(

[0] => a

[2] => b

[3] => h

[5] => d

[6] => t

)

المصفوفات

مثال ١٢

1. <?
2. `$a=array("a","a","b","h","a","d","t");`
3. `$b=array_values($a);`
4. `for($n=0;$n<count($b);$n++)`
5. `{`
6. `print("$b[$n]
\n");`
7. `}`
8. `?>`

التنفيذ

a

a

b

h

a

d

t

المصفوفات

مثال ١٣

1. <?
2. `$a=array("a","a","b","h","a","d","t");`
3. `asort($a);`
4. `print("<pre>");`
5. `print_r($a);`
6. `print("</pre>");`
7. ?>

التنفيذ

Array

(

[4] => a

[1] => a

[0] => a

[2] => b

[5] => d

[3] => h

[6] => t

)

المصفوفات

مثال ١٤

1. <?
2. `$a=array("a","a","b","h","a","d","t");`
3. `arsort($a);`
4. `print("<pre>");`
5. `print_r($a);`
6. `print("</pre>");`
7. ?>

التنفيذ

Array

(

[6] => t

[3] => h

[5] => d

[2] => b

[1] => a

[4] => a

[0] => a

)

المصفوفات

مثال ١٥

1. <?
2. \$a=array("a","a","b","h","a","d","t");
3. print("count of arrsy=");
4. print count(\$a);
5. print("
");
6. print("array is :");
7. for(reset(\$a);\$value=current(\$a);next(\$a))
8. {print("\$value
\n");}
9. if(in_array("b",\$a))
10. print "found b";
11. print "
";
12. if(in_array("k",\$a))
13. print "found k";
14. else
15. print "not found k";
16. ?>

التنفيذ

count of arrsy=7

array is :a

a

b

h

a

d

t

found b

not found k

الملفات

مثال ١

- `<html dir=rtl>`
- `<title>فتح و طباعة ملفات</title>`
- `<body>`
- `<? $f=fopen("a.txt","r");`
- `if!(($f))`
- `{ print("لم يتمكن من فتح الملف");`
- `exit; }`
- `while(!feof($f))`
- `{ $line=fgets($f,٢٥٥);`
- `print("$line
\n"); }`
- `fclose($f); ?>`
- `</body>`
- `</html>`

التنفيذ

fadwa
safiah

الملفات

مثال ٢

- `<html>`
- `<title> الكتابة إلى الملف </title>`
- `<body>`
- `<? $fp=fopen("log.txt","a");`
- `flock($fp,٢);`
- `fputs($fp,date("h:i a l F dS, Y\n"));`
- `flock($fp,٣);`
- `fclose($fp);`
- `print("<pre>");`
- `readfile("log.txt");`
- `print("</pre>\n");?>`
- `</body>`
- `</html>`

التنفيذ

09:34 am Monday November 06th, 2017

09:35 am Monday November 06th, 2017

09:35 am Monday November 06th, 2017

09:35 am Monday November 06th, 2017

09:35 am Monday November 06th, 2017

09:43 am Monday November 06th, 2017

11:30 am Sunday November 12th, 2017

01:26 pm Monday November 12th, 2018

01:30 pm Monday November 12th, 2018